



Glands




GL-33

3/4" NPT power cable gland for RAYSTAT-EX-02 (EEx d II C)
Nickel plated brass
For use with armoured power cables with outer sheath diameter of 12 mm - 21 mm and inner sheath diameter of 8.5 mm - 16 mm
PN 493217-000




GL-34

3/4" NPT power cable gland for RAYSTAT-EX-02 (EEx d II C)
Nickel plated brass
For use with non-armoured power cables with outer sheath diameter of 8.5 mm - 16 mm.
PN 931945-000




GL-36-M25

M25 power cable gland (EEx e)
Polyamide
For use with non-armoured power cables with outer diameter range 8 mm - 17 mm
Spare part for JBS-100, JBM-100 and JBU-100
PN 774424-000




GL-38-M25-METAL

M25 power cable gland (EEx e II and EEx d II C) for use with junction boxes with internal earth plate (-EP) or metal boxes.
For use with armoured power cables with sheath diameter of 12 mm - 21 mm and inner sheath diameter of 8.5 mm - 16 mm.
PN 056622-000



GL-44-M20-KIT


Cable gland EExe (M20), polyamide for use with PI cables with a diameter range of 5-13 mm. With green / yellow sleeve.
PN 1244-000 848



GL-45-M32


Cable gland EExe (M32), polyamide for use with power cables with a diameter range of 12-21 mm.
PN 1244-000 847

Adaptors



ADPT-PG16-M25-EEXE

Pg16 (female) to M25 (male) adaptor (EEx e)
Polyamide, ATEX approved adaptor with captive sealing ring ("o"-ring)
For use with cables with outer diameters up to 15 mm
PN 541892-000




REDUCER-M25/PG16-EEXE

M25 (female) to Pg16 (male) reducer (EEx e)
Polyamide, ATEX approved reducer with captive sealing ring ("o"-ring)
For use with cables with outer diameters up to 13 mm
PN 953780-000




REDUCER-M25/20-EEXD

M25 (male) to M20 (female) reducer EExd
Brass, ATEX approved reducer with captive sealing ring ("o"-ring)
PN 404287-000




REDUCER-M25/20


M25 (male) to M20 (female) reducer EEx d including a locknut and fibre washer
Brass, ATEX approved reducer with captive sealing ring ("o"-ring)
PN 630617-000



**REDUCER-M25/
M20-PA** M25 (male) to M20 (female) reducer for ordinary area
Polyamide
PN 184856-000




**REDUCER-M32/
M25-EEXE** M32 (male) to M25 (female) reducer (EEx e)
ATEX approved reducer. Polyamide.
PN 1244-000 859



**ADPT-M20/25-
EEXD** M20 (male) to M25 (female)
Brass, ATEX approved adaptor with captive sealing ring
("o"-ring)
For use with cables with outer diameters up to 14 mm
PN 684953-000

Small pipe adaptors with part number




JBS-SPA Small pipe adaptor required for pipes ≤ 1" (DN25),
applicable for JBS-100, E-100, E-100-L
E90515-000 (bag of 5 adaptors)

JBM-SPA Small pipe adaptor required for pipes ≤ 1" (DN25),
applicable for JBM-100, T-100
D55673-000 (bag of 5 adaptors)

Plugs




**HWA-PLUG-M20-
EXE-PLASTIC** M20 stopping plug EExe
Polyamide
Spare part for various junction boxes.
PN 1244-000 845




**HWA-PLUG-M25-
EXE-PLASTIC** M25 stopping plug
Polyamide
Spare part for JBS-100, JBM-100, JBU-100
PN 434994-000

Transmitter



TCONTROL-ISOL-01 ATEX approved isolator for MONI-PT100-4/20MA
Galvanically isolated module for EEx ia protection of
MONI-PT100-4/20MA sensor between the hazardous area and
the ordinary area. DIN 35 rail mounted.
A separate 24 Vdc power supply such as MONI-RMC-PS24 is
required.
PN 670021-000

Power supply



MONI-RMC-PS24 24 Vdc power supply
Wide range input (100-240 Vac) power supply to provide
24 Vdc input for MONI-RMC-BASE or TCONTROL-ISOL-01
products. Surface or DIN 35 rail mounted.
PN 972049-000